


Erbe ECO2™

# CO<sub>2</sub> Endoscopic Insufflator

Introducing a unique innovation from Erbe

The Erbe ECO2 CO<sub>2</sub> Endoscopic Insufflator is a medical device that delivers CO<sub>2</sub> via a gastrointestinal (GI) endoscope which reduces patient discomfort and post procedure recovery time. The user-friendly color touchscreen offers multiple options including a timer and various flow settings.



## FEATURES AND BENEFITS

CO<sub>2</sub> reduces patient discomfort and post procedure recovery time

Proprietary "Ultra-Low" flow setting and adjustable output flow rates including high, medium, and low

Safety features include pressure relief valves, audible alarms, and timed gas shut-off

Adjustable timer with four timer settings and automatic shut-off after: 30-60-90-120 minutes

Only compatible with ERBEFLO CleverCap® CO<sub>2</sub> or ERBEFLO AeroRinse® CO<sub>2</sub> Tubing Sets

- ☑ Color touchscreen with user-friendly interface
- ☑ Convenient tank graphic on screen visually represents remaining gas in tank
- ☑ Procedure data available under unit menu list

Erbe ECO2™

# CO<sub>2</sub> Endoscopic Insufflator

## Product Data

U.S. part number	Product	Description
7913-1000	ECO2 CO <sub>2</sub>	Endoscopic Insufflator (includes: yolk and hose)
7913-1001	ECO2 CO <sub>2</sub>	Endoscopic Insufflator Cart
7913-1002	ECO2 CO <sub>2</sub>	2 Tank Shuttle Valve

## Technical Data

Power Connection			
Rated supply voltage	Line Current	Power Fuses	Rated Supply Frequency
100-240VAC	500 mA	T 0.5 A, Slow blow	50 /60 Hz
Power input in standby mode		0.3 Watts	
Power input		20 Watts	
Terminal for grounding (potential equalization)		Yes	
Operating Characteristics			
Pre-sets		4 Pre-set flow rates and 4 pre-set timer options	
Continuous		No, when time ends the unit stops flowing	
Dimensions and weight			
Width x height x depth		5 1/2" x 6" x 14"	
Weight		< 15 lbs.	
Standards			
Classification according to EC Directive 93/42/EEC		II a	
Protection class as per EN 60601-1		I	
Type as per EN 60601-1		CF	
IP Rating		IP22	